

Broadcom L2 NDIS client driver: Capturing - Wireshark

File Edit View Go Capture Analyze Statistics Help

Filter: Expression... Clear Apply

No. -	Time	Source	Destination	Protocol	Info
1	0.000000	10.230.4.10	10.230.4.255	BROWSER	Local Master Announcement WBS101, workstation, Server, Domain Controller, Time source, NT workstation, M
2	39.489207	67.107.56.13	10.230.4.10	TCP	ismaeasdaqtest > http [SYN] Seq=0 win=65535 Len=0 MSS=1260
3	39.489234	10.230.4.10	67.107.56.13	TCP	http > ismaeasdaqtest [SYN, ACK] Seq=0 Ack=1 win=16384 Len=0 MSS=1460
4	39.493920	67.107.56.13	10.230.4.10	TCP	ismaeasdaqtest > http [ACK] Seq=1 Ack=1 win=65535 Len=0
5	47.809623	Sonicwal_0c:e4:75	Broadcast	ARP	who has 10.230.4.11? Tell 10.230.4.1
6	47.809637	de11_63:5a:e3	Sonicwal_0c:e4:75	ARP	10.230.4.11 is at 00:1d:09:63:5a:e3

Frame 3 (62 bytes on wire, 62 bytes captured)

- Ethernet II, Src: Dell_63:5a:e3 (00:1d:09:63:5a:e3), Dst: Sonicwal_0c:e4:75 (00:06:b1:0c:e4:75)
- Internet Protocol, Src: 10.230.4.10 (10.230.4.10), Dst: 67.107.56.13 (67.107.56.13)
- Transmission Control Protocol, Src Port: http (80), Dst Port: ismaeasdaqtest (1950), Seq: 0, Ack: 1, Len: 0

```

0000  00 06 b1 0c e4 75 00 1d 09 63 5a e3 08 00 45 00  ....U.. .cZ...E.
0010  00 30 52 e6 00 00 80 06 00 00 0a e6 04 0a 43 6b  .0R..... ..ck
0020  38 0d 00 50 07 9e cd e5 91 34 20 64 90 f1 70 12  8..P.... .4 d..p.
0030  40 00 a0 49 00 00 02 04 05 b4 01 01 04 02      @..I.....

```

Broadcom L2 NDIS client driver: <live capture in ... Packets: 6 Displayed: 6 Marked: 0 Profile: Default